



2022 SPEC SHEET

Newmar Dutch Star

Floor plans: 3717, 3736

5-STAR FEATURES



24/7 factory-direct phone support



ZF Independent Front Suspension with up to 60-Degree Wheel Cut: the tightest turning radius in the industry



Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system



Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel
Prioritizes driver safety



Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers



Increased towing capacity
Superior roll stability & handling
Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	450 HP @ 2,100 rpm
Torque	1,250 lb/ft
Brake	Engine Compression Brake (three stage)

WEIGHT RATINGS

Front GAWR	16,000 lbs
Rear GAWR	24,000 lbs
Tag GAWR	N/A
Total GVWR	40,000 lbs
Total GCWR	50,000 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	10 Gallon

SUSPENSION

Front	ZF
Wheel Cut	56 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	ZF
Rear	Detroit DA-RS-23.0-4

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Bendix Air Drum Brakes with ABS

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	242"

COOLING

Radiator	1,638 sq/inch, Side mounted
-----------------	-----------------------------

HITCH

Rating	5,000 lbs
---------------	-----------

TIRES

Make	Michelin X Line Energy Z
Front Size	315/80R 22.5 20-ply
Rear Size	315/80R 22.5 20-ply
Wheels	9" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display with Roadwatch and Tire Pressure Monitoring System
Safety	RoadWatch featuring Collision Mitigation (forward warning and active braking)(optional), Adaptive Cruise Control (ACC)(optional), Electronic Stability Control (ESC) with Roll Stability Control (RSC), Automatic Traction Control (ATC)

WARRANTY

Basic Chassis / Drivetrain	3 years, 50,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi



2022 SPEC SHEET

Newmar Dutch Star Tag

Floor plans: 4310, 4311, 4326, 4328, 4363, 4369

5-STAR FEATURES



24/7 factory-direct phone support



ZF Independent Front Suspension with up to 60-Degree Wheel Cut: the tightest turning radius in the industry



Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system



Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel
Prioritizes driver safety



Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers



Reduced curb-to-curb turning radius
Eliminates costly tire scrub
Fully integrated & precision tuned to coach model & floorplan



Increased towing capacity
Superior roll stability & handling
Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	450 HP @ 2,100 rpm
Torque	1,250 lb/ft
Brake	Engine Compression Brake (three stage)

WEIGHT RATINGS

Front GAWR	19,000 lbs
Rear GAWR	20,000 lbs
Tag GAWR	12,000 lbs
Total GVWR	51,000 lbs
Total GCWR	66,000 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	150 Gallon
Def Tank	15 Gallon

SUSPENSION

Front	ZF
Wheel Cut	52 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	ZF
Rear	Detroit DA-RS-21.0-4
Tag	UltraSteer

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	288"

COOLING

Radiator	1,638 sq/inch, Side mounted
-----------------	-----------------------------

HITCH

Rating	15,000 lbs
---------------	------------

TIRES

Make	Michelin XZA
Front Size	365/70R 22.5 20-ply
Rear Size	315/80R 22.5 20-ply
Tag Size	315/80R 22.5 20-ply
Wheels	10.5 front/9 rear" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel w/ dash controls
Instruments	OptiView LCD display w/ Roadwatch/TPMS
Safety	RoadWatch featuring Collision Mitigation (forward warning and active braking)(optional), Adaptive Cruise Control (ACC)(optional), Electronic Stability Control (ESC) with Roll Stability Control (RSC), Automatic Traction Control (ATC)

WARRANTY

Basic Chassis / Drivetrain	3 years, 50,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross	5 years, 100,000 mi



2022 SPEC SHEET

Newmar Dutch Star Tag

Floor plans: 4020, 4081

5-STAR FEATURES



24/7 factory-direct phone support



ZF Independent Front Suspension with up to 60-Degree Wheel Cut: the tightest turning radius in the industry



Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system



Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel
Prioritizes driver safety



Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers



Reduced curb-to-curb turning radius
Eliminates costly tire scrub
Fully integrated & precision tuned to coach model & floorplan



Increased towing capacity
Superior roll stability & handling
Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	450 HP @ 2,100 rpm
Torque	1,250 lb/ft
Brake	Engine Compression Brake (three stage)

WEIGHT RATINGS

Front GAWR	17,000 lbs
Rear GAWR	20,000 lbs
Tag GAWR	12,000 lbs
Total GVWR	49,000 lbs
Total GCWR	64,000 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	15 Gallon

SUSPENSION

Front	ZF
Wheel Cut	56 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	ZF
Rear	Detroit DA-RS-21.0-4
Tag	UltraSteer

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	252"

COOLING

Radiator	1,638 sq/inch, Side mounted
-----------------	-----------------------------

HITCH

Rating	15,000 lbs
---------------	------------

TIRES

Make	Michelin X Line Energy Z
Front Size	315/80R 22.5 20-ply
Rear Size	315/80R 22.5 20-ply
Tag Size	315/80R 22.5 20-ply
Wheels	9" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel w/ dash controls
Instruments	OptiView LCD display w/ Roadwatch/TPMS
Safety	RoadWatch featuring Collision Mitigation (forward warning and active braking)(optional), Adaptive Cruise Control (ACC)(optional), Electronic Stability Control (ESC) with Roll Stability Control (RSC), Automatic Traction Control (ATC)

WARRANTY

Basic Chassis / Drivetrain	3 years, 50,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross	5 years, 100,000 mi