



2022 SPEC SHEET

Newmar New Aire

Floor plans: 3541, 3543, 3545

5-STAR FEATURES



24/7 factory-direct phone support



ZF Independent Front Suspension with up to 60-Degree Wheel Cut: the tightest turning radius in the industry



Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system



Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel
Prioritizes driver safety



Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers



Increased towing capacity
Superior roll stability & handling
Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	450 HP @ 2,100 rpm
Torque	1,250 lb/ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	14,600 lbs
Rear GAWR	24,000 lbs
Tag GAWR	N/A
Total GVWR	38,600 lbs
Total GCWR	48,600 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	90 Gallon
Def Tank	15 Gallon

SUSPENSION

Front	ZF
Wheel Cut	60 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	ZF
Rear	Detroit DA-RS-23.0-4

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Bendix Air Drum Brakes with ABS

RAILS

Straight	9.125" x 2.81" x 0.3125"
-----------------	--------------------------

FRAME

Construction	Straight rail with lowered rear section
Wheel Base	226"

COOLING

Radiator	1,638 sq/inch, Side mounted
-----------------	-----------------------------

HITCH

Rating	5,000 lbs
---------------	-----------

TIRES

Make	Michelin XRV
Front Size	305/70R 22.5 20-ply
Rear Size	305/70R 22.5 20-ply
Wheels	9" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel w/ OptiView controls
Instruments	OptiView LCD with Roadwatch. Push Button Start and Tire Pressure Monitoring System
Safety	RoadWatch featuring Collision Mitigation (forward warning and active braking), Adaptive Cruise Control (ACC), Electronic Stability Control (ESC) with Roll Stability Support (RSS), Automatic Traction Control (ATC) and Mobileye Sensor Detection

WARRANTY

Basic Chassis / Drivetrain	3 years, 50,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi